



NOTES:

1. TORQUE RATINGS, Nm :

PART NUMBER	SYMMETRIC TORQUE
BH10-1003-10	1.0
BH10-1003-20	2.0
BH10-1003-30	3.0

2. CYCLE LIFE:
WITHIN 25,000 CYCLES STATIC TORQUE STAY WITHIN $\pm 25\%$ OF TORQUE SPECIFICATION.

3. FINISH: PLATING

4. 360 DEGREE SHAFT ROTATION

METRIC(MM)	[ENGLISH] (IN)	LEEEO		DWG NO.	
0-3 ± 0.15 3-10 ± 0.20 10-30 ± 0.25 30-50 ± 0.30 50-100 ± 0.40 100-200 ± 0.50	0-0.118 ± 0.006 0.118-0.394 ± 0.008 0.394-1.181 ± 0.010 1.181-2.000 ± 0.012 2.000-4.000 ± 0.016 4.000-8.000 ± 0.020			BH10-1003-xx	
PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION		BH10			
		APPROVED	DRAWN	STEEL	
JLIU	BCHEN	A3			
SHEET 1 OF 1		SCALE: 2.000			