



NOTES:

1. TORQUE RATINGS, Nm
SYMMETRIC TORQUE: 0.8, CW=CCW
2. CYCLE LIFE:
WITHIN 10,000 CYCLES STATIC TORQUE STAY WITHIN
±25% OF TORQUE SPECIFICATION.
3. FINISH: PLATING
4. 360 DEGREE SHAFT ROTATION

METRIC(MM) [ENGLISH] (IN)		<h1>LEEEO</h1>		DWG NO. BH8-1003-xx	
0-3 < ±0.15 3-10 < ±0.20 10-30 < ±0.25 30-50 < ±0.30 50-100 < ±0.40 100-200 < ±0.50	0-0.118 < ±0.006 0.118-0.394 < ±0.008 0.394-1.181 < ±0.010 1.181-2.000 < ±0.012 2.000-4.000 < ±0.016 4.000-8.000 < ±0.020			TITLE BH8	
PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION		APPROVED JLIU	DRAWN BCHEN	MATERIAL STEEL	
		SHEET 1 OF 1 SCALE: 2.000		REV A3	