



NOTES:

1. TORQUE RATINGS, Nm :

| PART NUMBER | SYMMETRIC TORQUE |
|---------------|------------------|
| CT10A-1025-09 | 0.9 |
| CT10A-1025-14 | 1.4 |
| CT10A-1025-18 | 1.8 |
| CT10A-1025-23 | 2.3 |
| CT10A-1025-27 | 2.7 |

| PART NUMBER | ASYMMETRIC CW TORQUE | ASYMMETRIC CCW TORQUE |
|---------------|----------------------|-----------------------|
| CT10A-2025-14 | 1.4 | 0.8 |
| CT10A-2025-18 | 1.8 | 1.1 |
| CT10A-2025-23 | 2.3 | 1.4 |
| CT10A-2025-27 | 2.7 | 1.6 |
| CT10A-2025-34 | 3.4 | 2.0 |
| CT10A-3025-14 | 0.8 | 1.4 |
| CT10A-3025-18 | 1.1 | 1.8 |
| CT10A-3025-23 | 1.4 | 2.3 |
| CT10A-3025-27 | 1.6 | 2.7 |
| CT10A-3025-34 | 2.0 | 3.4 |

2. CYCLE LIFE:
WITHIN 25,000 CYCLES STATIC TORQUE STAY WITHIN ±20% OF TORQUE SPECIFICATION.
3. FINISH: NATURE
4. 360 DEGREE SHAFT ROTATION

| METRIC(MM) | [ENGLISH] (IN) | LEEEO | | DWG NO. | | | |
|---|----------------------|--------------|-------|-------------------------|----------|----|-----|
| 0-3 < ±0.15 | 0-0.118 < ±0.006 | | | CT10A-x025-xx | | | |
| 3-10 < ±0.20 | 0.118-0.394 < ±0.008 | TITLE | | | | | |
| 10-30 < ±0.25 | 0.394-1.181 < ±0.010 | CT10A | | | | | |
| 30-50 < ±0.30 | 1.181-2.000 < ±0.012 | | | | MATERIAL | | |
| 50-100 < ±0.40 | 2.000-4.000 < ±0.016 | APPROVED | DRAWN | STEEL & ZINC | | | |
| 100-200 < ±0.50 | 4.000-8.000 < ±0.020 | JLIU | BCHEN | | | | |
| PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION | | SHEET 1 OF 1 | | SCALE: 2.500 | REV | A3 | ☉ □ |