



NOTES:

1. TORQUE RATINGS, Nm :

PART NUMBER	SYMMETRIC TORQUE
CT10B-1025-09	0.9
CT10B-1025-14	1.4
CT10B-1025-18	1.8
CT10B-1025-23	2.3
CT10B-1025-27	2.7

PART NUMBER	ASYMMETRIC CW TORQUE	ASYMMETRIC CCW TORQUE
CT10B-2025-14	1.4	0.8
CT10B-2025-18	1.8	1.1
CT10B-2025-23	2.3	1.4
CT10B-2025-27	2.7	1.6
CT10B-2025-34	3.4	2.0
CT10B-3025-14	0.8	1.4
CT10B-3025-18	1.1	1.8
CT10B-3025-23	1.4	2.3
CT10B-3025-27	1.6	2.7
CT10B-3025-34	2.0	3.4

2. CYCLE LIFE:
WITHIN 25,000 CYCLES STATIC TORQUE STAY WITHIN
±20% OF TORQUE SPECIFICATION.

3. FINISH: NATURE

4. 360 DEGREE SHAFT ROTATION

METRIC(MM)	[ENGLISH] (IN)	LEEEO		DWG NO.	
0-3 < ±0.15	0-0.118 < ±0.006			CT10B-x025-xx	
3-10 < ±0.20	0.118-0.394 < ±0.008	TITLE			
10-30 < ±0.25	0.394-1.181 < ±0.010	CT10B			
30-50 < ±0.30	1.181-2.000 < ±0.012	APPROVED	DRAWN	MATERIAL	
50-100 < ±0.40	2.000-4.000 < ±0.016	JLIU	BCHEN	STEEL & ZINC	
100-200 < ±0.50	4.000-8.000 < ±0.020			REV	
PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION		SHEET 1 OF 1	SCALE: 2.200	A3	☉ □